



<b>Permit #:</b>	
<b>House address or lot number:</b>	
<b>Walls</b>	<b>Blown or Sprayed Fiberglass or Cellulose - Walls</b>
Type of insulation:	R-value per inch:
Manufacturer:	Coverage area:
R-value:	Bag count:
<b>Floor</b>	<b>Blown or Sprayed Fiberglass or Cellulose - Ceiling</b>
Type of insulation:	R-value per inch:
Manufacturer:	Coverage area:
R-value:	Bag count:
<b>Flat Ceiling/Attic</b>	<b>Sprayed Polyurethane Foam (SPF)</b>
Type of insulation:	Density:
Manufacturer:	Installed thickness:
R-value:	R-value of installed thickness:
<b>Single Rafter Joist Vaulted Ceiling</b>	Building component installed: (circle one) walls floor ceiling
Type of insulation:	
Manufacturer:	
R-value:	
<b>Insulation Installer</b>	
Company name:	
Installer name:	
Installer signature:	
Date:	
Phone number:	
Email:	

[Washington State Energy Code Reference:](#)

**R303.1 Identification.** Materials, systems and equipment shall be identified in a manner that will allow a determination of compliance with the applicable provisions of this code.

**R303.1.1 Building thermal envelope insulation.** An R-value identification mark shall be applied by the manufacturer to each piece of building thermal envelope insulation 12 inches (305 mm) or greater in width. Alternately, the insulation installers shall provide a certification listing the type, manufacturer and R-value of insulation installed in each element of the building thermal envelope. For blown or sprayed insulation (fiberglass and cellulose), the initial installed thickness, settled thickness, settled R-value, installed density, coverage area and number of bags installed shall be listed on the certification. For sprayed polyurethane foam (SPF) insulation, the installed thickness of the areas covered and R-value of installed thickness shall be listed on the certification. For insulated siding, the R-value shall be labeled on the product’s package and shall be listed on the certification. The insulation installer shall sign, date and post the certification in a conspicuous location on the job site.

**Exception:** For roof insulation installed above the deck, the R-value shall be labeled as required by the material standards specified in Table 1508.2 of the *International Building Code* or Table R906.2 of the *International Residential Code*.